

MOTOTRBO™ SLR™ 5500 REPEATER



For your business to be successful, you need dependable voice and data communications that reach every corner of your operation. The MOTOTRBO SLR 5500 repeater delivers high performance, high reliability two-way radio service with all the features you need to connect your workplace.

With its sleek form factor and low power consumption, the SLR 5500 is engineered for low cost of ownership. And with a huge leap forward in technology, it represents the next generation in repeaters.

Versatile and powerful, MOTOTRBO combines the best of two-way radio functionality with the latest digital technology. It integrates voice and data seamlessly, offers advanced features that are easy to use and delivers increased capacity to meet your communication needs; from the field to the factory floor.

Whether you need the simplicity of a single site conventional system, simple site connectivity offered by IP Site Connect, or the powerful trunking capabilities of Capacity Plus and Capacity Max, the SLR 5500 delivers the power of digital two-way radio to your workforce. It can also operate as an analogue repeater (conventional or MPT 1327), or as a mixed-mode analogue/digital repeater while you transition away from a legacy analogue system.



NEXT GENERATION MOTOTRBO REPEATER

The SLR 5500 represents a huge leap forward in design and technology. Based on a wealth of field experience, customer feedback and technological innovation, the product delivers outstanding performance and efficiency for your business two-way radio system. From rock-solid reliability to clever touches like an integrated battery charger, the SLR 5500 is truly the next generation in repeaters.

HIGH PERFORMANCE

The SLR 5500 is designed to offer round-the-clock reliable operation, even at its continuous full transmit power of 50W. The high-quality design has been validated through Motorola Solutions Accelerated Life Testing (ALT) programme, and meets stringent quality criteria.

To deliver reliable coverage throughout your business premises, the product has a next-generation receiver design, with high sensitivity and improved noise blocking. Combined with the 50W transmit output power and digital error correction, this gives you clear voice quality, even in the most adverse conditions.

The SLR 5500 supports the full MOTOTRBO feature set, and is compatible with all the MOTOTRBO system architectures: single site conventional, IP Site Connect, Capacity Plus (single- and multi-site), and Capacity Max. The IP interface allows you to build applications and consoles directly into your system.

HIGH EFFICIENCY

The latest RF technology gives the SLR 5500 exceptionally good power efficiency. Together with its space-efficient 1U height and low thermal footprint, it gives you a very low cost of ownership.

The product has simple servicing requirements, with field-replaceable Power Amplifier, Power Supply and Modem modules. A front panel USB port allows easy configuration, with optional support for remote management. It also has built-in features such as a 3A battery charger, external alarm ports and an auxiliary power output to ease site installation.

The standard warranty is 2 years, and can be enhanced with one of our full service support programmes that protects your hardware investment with prioritised expert repair, proactive technical support, software updates and more.

DESIGNED FOR THE FUTURE

Motorola Solutions is committed to supporting you with even more sophisticated workforce communication solutions as your needs evolve, so the SLR 5500 is designed with the future in mind. Compared to first generation repeaters, it has 10x more processing power, 15x more memory and 125x more data storage. The architecture even has provision for expansion modules, should more functionality be required in the future.

MOTOTRBO SLR 5500

With excellent performance, high reliability and clever design in a small, slim unit, the SLR 5500 repeater is at the heart of a MOTOTRBO professional two-way radio system. To find out more, please contact your local authorised Motorola Solutions Channel Partner.





GENERAL SPECIFICATIONS

	VHF	UHF	300 MHz
Frequency Range	136-174 MHz	400-470 MHz	300-360 MHz
Channel Capacity		64	
RF Output Power		1-50 W	
Dimensions (H x W x D)		44 x 483 x 370 mm	
Weight		8.6 kg	
Input Voltage (AC)		100-240 Vac, 47-63 Hz	
Current (standby), 110 / 240 V		0.18 / 0.25 A	
Current (transmitting), 110 / 240 V		1.5 / 0.9 A	
Input Voltage (DC)		11.0-14.4 Vdc	
Current (standby)		0.7 A	
Current (transmitting)		9.5 A	
Operating Temperature Range		-30 to +60 °C	
Humidity		RH of 95%, non-condensing at 50 °C	
Max Duty Cycle		100%	
FCC Description	ABZ99FT3094	ABZ99FT4096	-
IC Description	109AB-99FT3094	109AB-99FT4096	-
Digital Vocoder Type		AMBE+2™	
Battery Charger Capacity		12 V, 3 A	
Connectivity		Tx (N female), Rx (BNC female), USB A receptacle, 2x Ethernet	
Supported System Types		Digital Conventional, IP Site Connect, Capacity Plus (Single Site and Multi-Site), Capacity Max, Analogue Conventional, MPT 1327	

RECEIVER

	136-174 MHz	400-470 MHz	300-360 MHz
Frequency Range	136-174 MHz	400-470 MHz	300-360 MHz
Channel Spacing		12.5 / 20 / 25 kHz	
Frequency Stability		0.5 ppm	
Sensitivity, 12dB SINAD		0.22 µV	
Sensitivity, 5% BER		0.22 µV	
Selectivity (TIA603D), 12.5/20/25 kHz	55 / 83 / 83 dB	55 / 80 / 80 dB	55 / 80 / 80 dB
Selectivity (TIA603), 12.5/20/25 kHz	68 / 83 / 83 dB	68 / 80 / 80 dB	68 / 80 / 80 dB
Selectivity (ETSI), 12.5/20/25 kHz		63 / 70 / 70 dB	
Intermodulation Rejection (TIA603D/ETSI)		82 / 73 dB	
Spurious Rejection (TIA603D/ETSI)		95 / 90 dB	
Audio Distortion		< 1%	
Transmitter Hum and Noise, 12.5/20/25 kHz		-45 / -45 / -50 dB	

TRANSMITTER

	136-174 MHz	400-470 MHz	300-360 MHz
Frequency Range	136-174 MHz	400-470 MHz	300-360 MHz
RF Output Power		1-50 W	
Max Duty Cycle		100%	
Channel Spacing		12.5 / 20 / 25 kHz	
Frequency Stability		+/- 0.5 ppm	
Intermodulation Attenuation		40 dB	
Adjacent Channel Power (TIA603D), 12.5/20/25 kHz		62 / 78 / 78 dB	
Adjacent Channel Power (ETSI), 12.5/20/25 kHz		62 / 78 / 78 dB	
Conducted Spurious Emissions		-36 dBm < 1 GHz, -30 dBm > 1 GHz	
Modulation Fidelity (4FSK)		FSK Error 5%, FSK Magnitude 1%	
Audio Response		TIA603D	
Audio Distortion		< 1%	
Receiver Hum and Noise, 12.5/20/25 kHz		-45 / -45 / -50 dB	
Rated System Deviation, 12.5/20/25 kHz		±2.5 / ±4.0 / ±5.0 kHz	



To get connected with MOTOTRBO, please contact your local Motorola Solutions representative or visit motorolasolutions.com/MOTOTRBO

Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, United Kingdom.

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2020 Motorola Solutions, Inc. All rights reserved. (11-20)

